



Patersons Precon, 6 Hornock Road, Coatbridge, ML5 2EU

25

0086-CPD-596387

EN 771-3:2011

**Category 1**, 440 x 215 x 215mm aggregate concrete hollow masonry unit - **Code HB215**

**Dimensions:** 440mm, 215mm, 215mm

**Dimensional Tolerances:** Category D1

**Configuration:** Group 2 Unit to EN1996-1-1

**Compressive Strength:** Characteristic 7.3 N/mm<sup>2</sup> [  $\perp$  Bed Face ]

**Dimensional Stability:** Moisture Movement Co-efficient 0.88 mm/m

**Shear Bond Strength:** Fixed Value 0.15 (N/mm<sup>2</sup>)

**Flexural Bond Strength:** NPD

**Reaction to fire:** Euroclass A1

**Water Vapour Diffusion Coefficient:** 5/15

**Direct airborne sound insulation:**

Gross dry density 1310 kg/m<sup>3</sup>

Configuration As above

**Thermal Conductivity:** 0,95 W/mK( $\lambda_{10,dry,unit,S1}$ )

**Durability against freeze-thaw:** Pass

**Dangerous Substances:** See Note below

NOTE Information on dangerous substances will only be given when and where required and in the appropriate form.

*Issue date - November 2025*